

INDUSTRIAL COMPONENT DATA

DILA-XHI10-S 115948 Y7-115948 EATON ELECTRIC Auxiliary contact module, 1N/O, side, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHI10-S



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHI10-S
Catalog number	Y7-115948
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-88EF134B4F
Generated	2026-08-04

Product Overview

Auxiliary contact module, 1N/O, side, screw connection

DILA-XHI10-S

Eaton Moeller® series DILA Auxiliary contact module, 1 pole, Ith= 16 A, 1 N/O, Side mounted, Screw terminals, DILA, DILM7 - DILM15

Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for standard applications, 1 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Mounting type: Side mounted, For use with: DILM7..., DILM9..., DILM12..., DILM15..., DILMP20..., DILA..., Type: Side-mounting auxiliary contacts , Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILM 7 - DILM32, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 115948 Model Code DILA-XHI10-S EAN 4015081156887 Product Length/Depth 66 mm Product Height 48 mm Product Width 15 mm Product

Weight 0.024 kg Certifications CE

CSA Class No.: 3211-03

CSA File No.: 012528

UL

VDE 0660

CSA

IEC/EN 60947

UL 508

UL File No.: E29184

UL Category Control No.: NKCR

IEC/EN 60947-4-1

CSA-C22.2 No. 14-05 Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions

For standard applications Fitted with: Switching elements according to EN 50005

Interlocked opposing contacts Number of poles Single-pole Electric connection type Screw connection General

Degree of protection IP20 Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting

method Side mounting Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection

against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC

6000 V Type Side-mounting auxiliary contacts Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature

(enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min -40 °C

Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cons...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHI10-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.