

INDUSTRIAL COMPONENT DATA

DILM150-XHI11 277946 Y7-277946 EATON ELECTRIC Auxiliary contact module, 1N/O+1N/C

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XHI11



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XHI11
Catalog number	Y7-277946
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-8041471C58
Generated	2026-08-04

Product Overview

Auxiliary contact module, 1N/O+1N/C

DILM150-XHI11

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170

Auxiliary contact module, with interlocked opposing contacts, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 6 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Front fixing, For use with: DILM40..., DILM50..., DILM65..., DILM72..., DILM80..., DILM95..., DILM115..., DILM150..., DILM170..., DILMP63..., DILMP80..., DILMP125..., DILMP160..., DILMP200..., DILMF40..., DILMF50..., DILMF65..., DILMF80..., DILMF95..., DILMF115..., DILMF150..., Type: Front mounting auxiliary contact, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 Appendix L, inside the auxiliary contact module, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM auxiliary contact module

Catalog Number 277946

Model Code DILM150-XHI11

EAN 4015082779467

UPC 782116354771

Product Length/Depth 39 mm

Product Height 46 mm

Product Width 24 mm

Product Weight 0.03 kg

Certifications IEC/EN 60947-4-1

CE

CSA

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

VDE 0660

UL

CSA File No.: 012528

IEC/EN 60947

CSA Class No.: 3211-03

UL 508

UL File No.: E29184

Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)

Functions For standard applications

Fitted with: Interlocked opposing contacts

Number of poles Two-pole

Number of poles Two-pole

Number of poles Two-pole

Electric connection type Screw connection

General information

Connection Screw terminals

Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A)

Model Top mounting

Mounting method Front fastening

Overvoltage category III

Pollution degree 3

Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp) 6000 V AC

Type Front mounting auxiliary contact

Ambient conditions, mechanical

Shock resistance 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Climatic environmental conditions

Ambient operating temperature - min -...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XHI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.