

INDUSTRIAL COMPONENT DATA

DILM820-XHI11-SI 208281 Y7-208281 EATON ELECTRIC

Auxiliary contact module 1 N/O + 1N/C laterally inside screw..

Brand: EATON - MOELLER | Manufacturer Part Number: DILM820-XHI11-SI



Manufacturer	EATON - MOELLER
MPN / Reference	DILM820-XHI11-SI
Catalog number	Y7-208281
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-BC181C5279
Generated	2026-08-05

Product Overview

Auxiliary contact module;1 N/O + 1N/C;laterally inside;screw connection

DILM820-XHI11-SI

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM250 - DILH2600, SI

Auxiliary contact module, with interlocked opposing contacts, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 500 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILM250 - DILH2600, DILDC300 - DILDC600, Type: Side-mounting auxiliary contacts, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 Appendix L, inside the auxiliary contact module , Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM auxiliary contact module Catalog Number 208281 Model Code

DILM820-XHI11-SI EAN 4015082082819 Product Length/Depth 77 mm Product Height 77 mm Product Width 15 mm

Product Weight 0.037 kg Certifications CSA File No.: 012528

UL File No.: E29184

CSA-C22.2 No. 14-05

IEC/EN 60947

VDE 0660

IEC/EN 60947-4-1

UL

CE

CSA

UL 508

UL Category Control No.: NKCR

CSA Class No.: 3211-04 Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions

For standard applications Fitted with: Interlocked opposing contacts Number of poles Two-pole Electric connection type

Screw connection General

Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting method Side mounting

Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact

when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC

6000 V Type Side-mounting auxiliary contacts Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Ambient operating temperature

(enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min -40 °C

Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capaci...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM820-XHI11-SI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.