

INDUSTRIAL COMPONENT DATA

DILM32-XHI11-S 101371 Y7-101371 EATON ELECTRIC

Auxiliary contact module, 1N/O+1N/C, side, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XHI11-S



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XHI11-S
Catalog number	Y7-101371
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-C27F79730E
Generated	2026-08-04

Product Overview

Auxiliary contact module, 1N/O+1N/C, side, screw connection

DILM32-XHI11-S

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM17 - DILM38

Auxiliary contact module, with interlocked opposing contacts, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILM17..., DILM25..., DILM32..., DILM38..., DILMF8..., DILMF11..., DILMF14..., DILMF17..., DILMF25..., DILMF32..., Type: Side-mounting auxiliary contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM auxiliary contact module Catalog Number 101371 Model Code

DILM32-XHI11-S EAN 4015081013067 Product Length/Depth 77 mm Product Height 77 mm Product Width 15 mm Product

Weight 0.038 kg Certifications UL Category Control No.: NKCR

CSA

CSA Class No.: 3211-04

IEC/EN 60947

UL
VDE 0660
CE
CSA File No.: 012528
CSA-C22.2 No. 14-05
IEC/EN 60947-4-1
UL 508
UL File No.: E29184 Catalog Notes Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified. Features & Functions
Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions
For standard applications Fitted with: Interlocked opposing contacts Number of poles Two-pole Electric connection type
Screw connection General
Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting method Side mounting
Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact
when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V
6000 V AC Type Side-mounting auxiliary contacts Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min -40 °C
Ambient storage temperature -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XHI11-S with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.