

INDUSTRIAL COMPONENT DATA

DILM150-XHIA11 283463 Y7-283463 EATON ELECTRIC

Auxiliary contact module, 1N/O+1N/C, surface mounting, screw ..

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XHIA11



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XHIA11
Catalog number	Y7-283463
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-7D24F2FBC0
Generated	2026-08-04

Product Overview

Auxiliary contact module, 1N/O+1N/C, surface mounting, screw connection

DILM150-XHIA11

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM auxiliary contact module Catalog Number 283463 Model Code

DILM150-XHIA11 EAN 4015082834630 Product Length/Depth 39 mm Product Height 46 mm Product Width 24 mm

Product Weight 0.03 kg Certifications IEC/EN 60947-4-1

CSA-C22.2 No. 14-05

UL

CSA Class No.: 3211-03

UL File No.: E29184

CE

CSA

IEC/EN 60947

UL 508

VDE 0660

CSA File No.: 012528

UL Category Control No.: NKCR Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions

For standard applications Fitted with: Interlocked opposing contacts Number of poles Two-pole Electric connection type

Screw connection General

Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting method Front fastening

Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact

when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Type Front mounting auxiliary contact Ambient conditions, mechanical

Shock resistance 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min -25 °C Amb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XHIA11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.