

INDUSTRIAL COMPONENT DATA

DILA-XHI13 276425 Y7-276425 EATON ELECTRIC Auxiliary contact module, 1N/O+3N/C, surface mounting, screw conn..

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHI13



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHI13
Catalog number	Y7-276425
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-FD04183DB4
Generated	2026-08-06

Product Overview

Auxiliary contact module, 1N/O+3N/C, surface mounting, screw connection

DILA-XHI13

Eaton Moeller® series DILA Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 3 NC, Front fixing, Screw terminals, DILA, DILM7 - DILM38

Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 3 NC, Mounting type: Front fixing, For use with: DILA(C)...., DILM(C)7..., DILM(C)9..., DILM(C)12..., DILM(C)15..., DILM(C)17..., DILM(C)25..., DILM(C)32..., DILM38..., DILMP20..., DILMP32..., DILMP45..., DILL..., DILMF8..., DILMF11..., DILMF14..., DILMF17..., DILMF25..., DILMF32..., Type: Fron

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 276425 Model Code DILA-XHI13 EAN 4015082764258 Product Length/Depth 45 mm Product Height 38 mm Product Width 36 mm Product Weight 0.048 kg Certifications CSA

CSA-C22.2 No. 14-05

VDE 0660

IEC/EN 60947

IEC/EN 60947-4-1

CSA File No.: 012528

CE

UL

UL File No.: E29184

UL 508

UL Category Control No.: NKCR

CSA Class No.: 3211-03 Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions

For standard applications Fitted with: Switching elements according to EN 50005

Interlocked opposing contacts Number of poles Four-pole Electric connection type Screw connection General

Degree of protection IP20 Shock resistance 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Lifespan, mechanical

10,000,000 Operations (DC operated)

10,000,000 Operations (AC operated) Model Top mounting Mounting method Front fastening Connection Screw terminals

Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact when actuated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHI13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.