

## INDUSTRIAL COMPONENT DATA

# DILM32-XHI22 277377 Y7-277377 EATON ELECTRIC Auxiliary contact module, 2N/O+2N/C

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XHI22



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | EATON - MOELLER         |
| MPN / Reference | DILM32-XHI22            |
| Catalog number  | Y7-277377               |
| Category        | Auxiliary contact block |
| Minimum order   | 5 Pcs                   |
| Document ID     | EO-BE3CFA67E0           |
| Generated       | 2026-08-03              |

## Product Overview

Auxiliary contact module, 2N/O+2N/C

DILM32-XHI22

Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM7-10 - DILM38-10

Auxiliary contact module, with interlocked opposing contacts, Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Mounting type: Front fixing, For use with: DILM(C)7-10..., DILM(C)9-10..., DILM(C)12-10..., DILM(C)15-10..., DILM(C)17-10..., DILM(C)25-10..., DILM(C)32-10..., DILM38-10..., DILMP20..., DILMP32-10..., DILMP45-10..., DILL..., DILMF8-10..., DILMF11-10..., DILMF14-10..., DILMF17-10..., DILMF25-10..., DILMF32-10..., Type: Front mounting auxiliary contact, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILM 7 - DILM32, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Contactors up to 170A

## Additional Product Information

Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM7-10 - DILM38-10 Auxiliary contact module, with interlocked opposing contacts, Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Mounting type: Front fixing,

For use with: DILM(C)7-10..., DILM(C)9-10..., DILM(C)12-10..., DILM(C)15-10..., DILM(C)17-10..., DILM(C)25-10..., DILM(C)32-10..., DILM38-10..., DILMP20..., DILMP32-10..., DILMP45-10..., DILL..., DILMF8-10..., DILMF11-10..., DILMF14-10..., DILMF17-10..., DILMF25-10..., DILMF32-10... , Type: Front mounting auxiliary contact, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILM 7 - DILM32, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

General specificationsProduct nameEaton Moeller® series DILM auxiliary contact modulePart

no.DILM32-XHI22EAN4015082773779Product Length/Depth45 millimetreProduct height38 millimetreProduct width36 millimetreProduct weight0.048 kilogramCertificationsCSA-C22.2 No. 14-05

CSA File No.: 012528

UL File No.: E29184

IEC/EN 60947

UL 508

CSA

CSA Class No.: 3211-03

VDE 0660

UL

CE

IEC/EN 60947-4-1

UL Category Control No.: NKCRProduct Tradename...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XHI22 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.