

INDUSTRIAL COMPONENT DATA

DILA-XHIR22 139580 Y7-139580 EATON ELECTRIC Auxiliary contact module, 2N/O+2N/C, electronic

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHIR22



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHIR22
Catalog number	Y7-139580
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-F9F84CA6B7
Generated	2026-08-05

Product Overview

Auxiliary contact module, 2N/O+2N/C, electronic

DILA-XHIR22

Eaton Moeller® series DILA Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Microswitch, Front fixing, Screw terminals, DILA, DILM7 - DILM38

Auxiliary contact module, with interlocked opposing contacts, (except microswitches), Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for standard applications, for electronic applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O (1 N/O above microswitch for electronic applications) , Contacts N/C = Normally closed: 2 NC (1 NC above microswitch for electronic applications), Mounting type: Front fixing, For use with: DILA(C)..., DILM(C)7..., DILM(C)9..., DILM(C)12..., DIL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 139580 Model Code DILA-XHIR22 EAN 4015081363582 Product Length/Depth 45 mm Product Height 42 mm Product Width 36 mm Product Weight 0.05 kg Certifications CE
UL File No.: E29184

VDE 0660

CSA Class No.: 3211-03

UL 508

IEC/EN 60947

CSA

CSA File No.: 012528

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

IEC/EN 60947-4-1

UL Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions
For electronic applications

For standard applications Fitted with: Switching elements according to EN 50005

Interlocked opposing contacts Number of poles Four-pole Electric connection type Screw connection General

Degree of protection IP20 Shock resistance 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical,
according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A)

1,300,000 Operations (at DC-12, 24 V / 50 mA) Lifespan, mechanical 10,000,000 Operations (DC operated)

10,000,000 Operations (AC operated) Model Top mounting Mounting method Front fastening Operating frequency 9000

Operations/h Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHIR22 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.