

INDUSTRIAL COMPONENT DATA

DILA-XHI40 276428 Y7-276428 EATON ELECTRIC Auxiliary contact module, 4N/O, surface mounting, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHI40



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHI40
Catalog number	Y7-276428
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-B82B58EED4
Generated	2026-08-05

Product Overview

Auxiliary contact module, 4N/O, surface mounting, screw connection

DILA-XHI40

Auxiliary contact module, 4 pole, Ith= 16 A, 4 N/O, Front fixing, Screw terminals, DILA, DILM7 - DILM38

Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Mounting type: Front fixing, For use with: DILA(C)..., DILM(C)7..., DILM(C)9..., DILM(C)12..., DILM(C)15..., DILM(C)17..., DILM(C)25..., DILM(C)32..., DILM38..., DILMP20..., DILMP32..., DILMP45..., DILL..., DILMF8..., DILMF11..., DILMF14..., DILMF17..., DILMF25..., DILMF32..., Type: Front mounting auxiliary contact, Instruct

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 276428 Model Code DILA-XHI40 EAN 4015082764289 Product Length/Depth 45 mm Product Height 38 mm Product Width 36 mm Product Weight 0.049 kg Certifications CE
UL 508

UL File No.: E29184

CSA

IEC/EN 60947-4-1

UL

VDE 0660

CSA-C22.2 No. 14-05

IEC/EN 60947

CSA Class No.: 3211-03

CSA File No.: 012528

UL Category Control No.: NKCR Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions

For standard applications Fitted with: Interlocked opposing contacts

Switching elements according to EN 50005 Number of poles Four-pole Electric connection type Screw connection General Degree of protection IP20 Shock resistance 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Lifespan, mechanical 10,000,000 Operations (AC operated)

10,000,000 Operations (DC operated) Model Top mounting Mounting method Front fastening Connection Screw terminals

Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact when actuated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHI40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.