

INDUSTRIAL COMPONENT DATA

DILA-XHIT20 101042 Y7-101042 EATON ELECTRIC Auxiliary contact module, raised, 2N/O, surface mounting, screw ..

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHIT20



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHIT20
Catalog number	Y7-101042
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-A545C043C6
Generated	2026-08-04

Product Overview

Auxiliary contact module, raised, 2N/O, surface mounting, screw connection

DILA-XHIT20

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC

Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for combination with electrical wiring links, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Mounting type: Front fixing, For use with: DILM7..., DILM9..., DILM12..., DILM15..., DILL..., MSC-D...M7(9, 12, 15)..., MSC-R...M7(9, 12) , Type: high version, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, al

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 101042 Model Code DILA-XHIT20 EAN 4015081009374 Product Length/Depth 55 mm Product Height 38 mm Product Width 36 mm Product Weight 0.039 kg Certifications CE
CSA Class No.: 3211-03

UL 508

UL

UL File No.: E29184

CSA

IEC/EN 60947-4-1

VDE 0660

CSA File No.: 012528

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

IEC/EN 60947 Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions

For combination with electrical wiringlinks Fitted with: Switching elements according to EN 50005

Interlocked opposing contacts Number of poles Two-pole Electric connection type Screw connection General

Degree of protection IP20 Shock resistance 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting

method Front fastening Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection

against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC

6000 V Type Front mounting auxiliary contact, high version Climatic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHIT20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.