

INDUSTRIAL COMPONENT DATA

VHI20-PKZ01 278495 Y7-278495 EATON ELECTRIC Auxiliary contact, operates as an early-make contact, 2N/O early

Brand: EATON - MOELLER | Manufacturer Part Number: VHI20-PKZ01



Manufacturer	EATON - MOELLER
MPN / Reference	VHI20-PKZ01
Catalog number	Y7-278495
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-C46220215A
Generated	2026-08-06

Product Overview

Auxiliary contact, operates as an early-make contact, 2N/O early

VHI20-PKZ01

Eaton Moeller® series PKZ01 Auxiliary contact, operates as an early-make contact, 2N/O early

Auxiliary contact, Contacts N/O = Normally open: 2 N/O, For use with: PKZM01

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ01 Accessory Auxiliary contact Catalog Number 278495 Model Code VHI20-PKZ01 EAN 4015082784959 Product Length/Depth 28 mm Product Height 40 mm Product Width 45 mm Product Weight 0.021 kg Certifications IEC/EN 60947-4-1

CE

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA

CSA File No.: 165628

UL File No.: E36332

CSA-C22.2 No. 14

UL

UL 508 Catalog Notes For the premature voltage application of the U-release, e.g. in EMERGENCY STOP circuits according to EN 60204. Features & Functions

Electric connection type Screw connection General

Lifespan, electrical 100,000 Operations Lifespan, mechanical 100,000 Operations Model Top mounting Mounting method

Front fastening Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 4000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 1.5 mm² Terminal capacity (solid/stranded AWG) 18 - 16 Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 1 A Rated operational current (Ie) at DC-13, 24 V 2 A Rated

operational voltage (Ue) at AC - max 440 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation 440 V,

Between auxiliary contacts and main contacts, According to EN 61140 Short-circuit protection rating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / VHI20-PKZ01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.