

## INDUSTRIAL COMPONENT DATA

# MCB-HK-SWD 177175 Y7-177175 EATON ELECTRIC Auxiliary contact, SmartWire-DT

Brand: EATON - MOELLER | Manufacturer Part Number: MCB-HK-SWD



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                 |
| MPN / Reference | MCB-HK-SWD                                      |
| Catalog number  | Y7-177175                                       |
| Category        | Auxiliary device for distribution board devices |
| Minimum order   | 1 Pcs                                           |
| Document ID     | EO-C901FB8AA1                                   |
| Generated       | 2026-08-03                                      |

## Product Overview

Auxiliary contact, SmartWire-DT

MCB-HK-SWD

Eaton Distribution parts. Auxiliary contact, SmartWire-DT

Screwless mounting, can be mounted on (retrofitted on) residual current circuit-breaker by snapping it into place (right-hand side), miniature circuit-breaker and combination (left), not for residual current circuit-breaker block, information output: ON, OFF, tripped

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                               |
|--------------|---------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Modular Switchgear - Others and Accessories |
|--------------|---------------------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 177175 Model Code MCB-HK-SWD EAN 4015081716197 Product Length/Depth 88.3 mm Product Height 74.7 mm Product Width 29.9 mm Product Weight 0.04 kg Compliances RoHS conform Product specifications

Used with SWD interface module

Accessory

Accessory for miniature circuit breaker

Accessory for residual current circuit breaker

Accessory for combined residual current/power circuit breaker Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type SWD interface module Mounting method For fitting on left to: FI

For fitting on right to: LS, FI/LS Additional equipment required Signaling switch Ambient operating temperature - max 40 °C  
Ambient operating temperature - min -5 °C Assembly width 1 TE Number of contacts (change-over contacts) 0 Number of  
contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Number of poles at main contact unit -  
max 0 Number of switches (fault signal) 0 Voltage type DC Functions Auxiliary switch Device fitting Universal Rated  
operational voltage (Ue) - max 15 V Rated switch current 0.0263 A Suitable for current of main contact unit - max 0 A  
ETIM for 177175 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Universal

Function (EF000030)

Auxiliary switch

Width in number of modular spacings (EF002950)

1

Number of contacts as normally open contac...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MCB-HK-SWD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.