

INDUSTRIAL COMPONENT DATA

C10-SLS/32/3 112223 65A3137G13 EATON ELECTRIC Fuse disconnectors, 32A, 3 p, 10 x 38

Brand: EATON - MOELLER | Manufacturer Part Number: C10-SLS/32/3



Manufacturer	EATON - MOELLER
MPN / Reference	C10-SLS/32/3
Catalog number	65A3137G13
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-8AA25B4BB3
Generated	2026-08-01

Product Overview

Fuse disconnectors, 32A, 3 p, 10 x 38

Fuse switch-disconnector, the flash function indicates the blowing of fuse link, sealable, double conductor run possible on both sides, /L type with flashing function, suitable for cylindrical fuses with application category gG, aM, supplied without fuses, types conform to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 112223 Model Code C10-SLS/32/3 EAN 4015081117819 Product Length/Depth 85 mm Product Height 70.8 mm Product Width 52.5 mm Product Weight 0.18 kg Compliances RoHS conform Product specifications

Rated uninterrupted current (Iu) 32 A Conditioned rated short-circuit current Iq 100 kA Number of poles Three-pole Rated operation power at AC-23, 400 V 0 kW Rated short-time withstand current (Icw) 0.3 kA Electrical connection type of main circuit Screw connection Actuator position Front side Actuator type Other Suitable for Ground mounting Rated conditional short-circuit current (Iq) 100 kA Suitable for fuses Shape C1-C3 Cable entry type Other Degree of protection (front side) IP20 Power rating at AC-23, 400 V 0 kW Rated operating voltage (Ue) at AC - max 690 V ETIM for 112223 Low-voltage industrial controls and switchgear (EC001040)

Feature Name

Feature Value

Version as main switch (EF006981)
No
Version as safety switch (EF006985)
No
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
32 A
Rated operation power at AC-23, 400 V (EF007027)
0 kW
Conditioned rated short-circuit current Iq (EF001444)
100 kA
Rated short-time withstand current Icw (EF007050)
0.3 kA
Suitable for fuses (EF006692)
Shape C1-C3
Number of poles (EF001391)
3
With error protection (EF007384)
No
Type of electrical connection of main circuit (EF006819)
Screw connection
Cable entry (EF000537)
Other
Equippe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C10-SLS/32/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.