

INDUSTRIAL COMPONENT DATA

Z-SH/3N 263880 Y7-263880 EATON ELECTRIC Fuse disconnectors, 3pole+N, 10 x 38

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SH/3N



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SH/3N
Catalog number	Y7-263880
Category	Fuse switch disconnecter
Minimum order	4 Pcs
Document ID	EO-A4276FD825
Generated	2026-08-04

Product Overview

Fuse disconnectors, 3pole+N, 10 x 38

Z-SH/3N

Eaton Distribution parts. Fuse disconnectors, 3pole+N, 10 x 38

Fuse disconnecter for industrial applications, without visual trip indication, for cylindrical fuse inserts, sealable, supplied without fuses, type conforms to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 263880 Model Code Z-SH/3N EAN 4015082638801 Product Length/Depth 80 mm Product Height 74 mm Product Width 52.5 mm Product Weight 0.24 kg Compliances RoHS conform Product specifications

Rated operational power at AC-23A, 400 V, 50 Hz 0 kW Rated permanent current (Iu) 32 A Rated uninterrupted current (Iu) 32 A Conditioned rated short-circuit current Iq 10 kA Number of poles Four-pole Rated operation power at AC-23, 400 V 0 kW Rated short-time withstand current (Icw) 0 kA Electrical connection type of main circuit Screw connection Actuator position Front side Actuator type Other Rated conditional short-circuit current (Iq) 10 kA Suitable for fuses Shape C1-C3 Cable entry type Other Degree of protection (front side) IP20 Power rating at AC-23, 400 V 0 kW Rated operating voltage (Ue) at AC - max 400 V

ETIM for 263880 Low-voltage industrial controls and switchgear (EC001040)

Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as safety switch (EF006985)
No
Max. rated operation voltage Ue AC (EF007355)
400 V
Rated permanent current Iu (EF001389)
32 A
Rated operation power at AC-23, 400 V (EF007027)
0 kW
Conditioned rated short-circuit current Iq (EF001444)
10 kA
Rated short-time withstand current Icw (EF007050)
0 kA
Suitable for fuses (EF006692)
Shape C1-C3
Number of poles (EF001391)
4
With error protection (EF007384)
No
Type of electrical connection of main circuit (EF006819)
Screw conn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SH/3N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.