

INDUSTRIAL COMPONENT DATA

Z-SHL/2 263885 Y7-263885 EATON ELECTRIC Fuse disconnectors, 2 p, 10 x 38

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SHL/2



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SHL/2
Catalog number	Y7-263885
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C2AC11E1E3
Generated	2026-08-04

Product Overview

Fuse disconnectors, 2 p, 10 x 38

Z-SHL/2

Z-SHL/2. Fuse disconnectors, 2 p, 10 x 38

Fuse disconnecter for industrial applications, with visual trip indication, for cylindrical fuse inserts, sealable, supplied without fuses, type conforms to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 263885 Model Code Z-SHL/2 EAN 4015082638856 Product Length/Depth 80 mm Product Height 74 mm Product Width 35 mm Product Weight 0.164 kg Compliances RoHS conform Product specifications

Rated uninterrupted current (Iu) 32 A Conditioned rated short-circuit current Iq 10 kA Number of poles Two-pole Rated operation power at AC-23, 400 V 0 kW Rated short-time withstand current (Icw) 0 kA Electrical connection type of main circuit Screw connection Actuator position Front side Actuator type Other Rated conditional short-circuit current (Iq) 10 kA Suitable for fuses Shape C1-C3 Cable entry type Other Degree of protection (front side) IP20 Power rating at AC-23, 400 V 0 kW Rated operating voltage (Ue) at AC - max 400 V

ETIM for 263885 Low-voltage industrial controls and switchgear (EC001040)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as safety switch (EF006985)

No

Max. rated operation voltage Ue AC (EF007355)

400 V

Rated permanent current Iu (EF001389)

32 A

Rated operation power at AC-23, 400 V (EF007027)

0 kW

Conditioned rated short-circuit current Iq (EF001444)

10 kA

Rated short-time withstand current Icw (EF007050)

0 kA

Suitable for fuses (EF006692)

Shape C1-C3

Number of poles (EF001391)

2

With error protection (EF007384)

No

Type of electrical connection of main circuit (EF006819)

Screw connection

Cable entry (EF000537)

Other

Equipped with connectors (EF011696)

No

Suitable for f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SHL/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.