


INDUSTRIAL COMPONENT DATA

AZ-XAA(12-60VAC) 212061 Y7-212061 EATON ELECTRIC

Shunt release, up to 125 A, 12-60V, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: AZ-XAA(12-60VAC)



Manufacturer	EATON - MOELLER
MPN / Reference	AZ-XAA(12-60VAC)
Catalog number	Y7-212061
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-20BCC85F40
Generated	2026-08-06

Product Overview

Shunt release, up to 125 A, 12-60V, 1HP

AZ-XAA(12-60VAC)

Eaton Distribution parts. Shunt release, up to 125A, 12-60V, 1HP

Shunt release, for MCB up to 125A, voltage range 12-110V AC / 12-60V DC, rated insulation voltage 440V AC, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1x1-25 mm² / 2x1-4 mm² solid and flexible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Modular Switchgear - Others and Accessories**

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 212061 Model Code AZ-XAA(12-60VAC) EAN 4015082120610
Product Length/Depth 80 mm Product Height 75 mm Product Width 39.1 mm Product Weight 0.159 kg Compliances RoHS conform Product specifications

Type Special features IP20 (switch) Accessory/spare part type Shunt release Degree of protection IP40 Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Used with Accessory

Accessory for miniature circuit breaker Admissible back-up fuse Inherently short-circuit-proof Mounting method Top-hat rail IEC/EN 60715 Additional equipment required Shunt release (for power circuit breaker) Terminal protection Protection against electric shock to IEC 536 Terminal type Twin-purpose terminals Voltage range 12 V AC - 60 V AC Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 1 TE Enclosure width 90 mm

Inrush current at AC 38 A Inrush current at DC 34 A Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Pick-up time AC 2.1 ms Rated insulation voltage (Ui) 440 VAC Voltage type AC/DC Functions Shunt release (for power circuit breaker) Duty factor 2 ms Device fitting Miniature circuit breaker (MCB) Mounting width 17.5 mm (1 space unit) Lifespan, mechanical 4000 operations Rated operational voltage....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AZ-XAA(12-60VAC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.