

INDUSTRIAL COMPONENT DATA

AZ-XHI11 212067 Y7-212067 EATON ELECTRIC Auxiliary contact, for AZ, 1N/O+1N/C, 0.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: AZ-XHI11



Manufacturer	EATON - MOELLER
MPN / Reference	AZ-XHI11
Catalog number	Y7-212067
Category	Auxiliary device for distribution board devices
Minimum order	6 Pcs
Document ID	EO-4599D042AE
Generated	2026-08-06

Product Overview

Auxiliary contact, for AZ, 1N/O+1N/C, 0.5HP

AZ-XHI11

Eaton Distribution parts. Auxiliary contact, for AZ, 1N/O+1N/C, 0.5HP

AZ, + 1N/O for 1N/C, 0.5auxiliary contacts, for AZ, 1N/O+1N/C, 0.5 SU auxiliary contact, 1N/O+1N/CSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 212067 Model Code AZ-XHI11 EAN 4015082120672 Product Length/Depth 90 mm Product Height 65.5 mm Product Width 8.8 mm Product Weight 0.041 kg Compliances RoHS conform Certifications CSA Certified

UL Listed

EN45545-2

IEC 61373 Product specifications

Type Special features IP20 (switch) Accessory/spare part type Auxiliary contacts Degree of protection IP40 Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Used with Type AZ breakers

Accessory

Accessory for miniature circuit breaker Mounting method Top-hat rail IEC/EN 60715 Additional equipment required Auxiliary switch Admissible back-up fuse - max 6 A gL Terminal protection Protection against electric shock to IEC 536 Terminal type

Twin-purpose terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Enclosure width 90 mm Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 2 Number of switches (fault signal) 0 Rated insulation voltage (Ui) 440 VAC Voltage type AC Functions Auxiliary switch Contact function 1 M + 1 B Device fitting Universal Mounting width 8.8 mm (0.5 space units) Lifespan, mechanical 6000 operations Rated operational voltage (Ue) - max 230 V Rated switch current 3 A Suitable for current of main contact unit - max 0 A Voltage rating (V/...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AZ-XHI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.