

INDUSTRIAL COMPONENT DATA

SL4-SWD 171311 Y7-171311 EATON ELECTRIC Base module connection to SmartWire-DT

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-SWD



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-SWD
Catalog number	Y7-171311
Category	Connection module for signal tower
Minimum order	1 Pcs
Document ID	EO-7241DCEB03
Generated	2026-08-05

Product Overview

Base module;connection to SmartWire-DT

SL4-SWD

Eaton Moeller® series SL4 Base module;connection to SmartWire-DT

Base module, Color black, Aluminum color tube, Product range: SL signal towers, SmartWire-DT slave, Subrange:

SmartWire-DT Signal towers, Connection technique: Blade terminal SWD4-8MF2, Mounting type: for horizontal mounting,

Fitted with: Base with base adapter for slipping onto place (rapid mounting and wiring system), including cover, Tube length:

100 mm, Description: External power supply connectable (24 V DC), Configurable with SWD-Assist (planning and ordering

tool), Further technical data, see manual MN05006001Z., Number of modules: max. 5 modules, max. 0.3 A per module, For

use with: SL4-L-..., SL4-BL-..., SL4-FL-..., SL4-AP-..., Connection to SmartWire-DT: yes, Standards: IEC/EN 60947-5-1,

IEC degree of protection: IP66, IEC/EN 60529, Protection type UL: Type 4, 4X, 13

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Base module Catalog Number 171311 Model Code SL4-SWD EAN

4015081678525 Product Length/Depth 81 mm Product Height 145 mm Product Width 81 mm Product Weight 0.172 kg

Certifications IEC/EN 60947-5-1

CE

CSA-C22.2 No. 94-91

UL 508

CSA-C22.2 No. 14-10

IEC/EN 60529 Features & Functions

Color Other Fitted with: Cover

Base adapter for slipping onto place (rapid mounting and wiring system) Number of modules Max. 5 (0.3 A per module)

Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base) General

Connection to SmartWire-DT Yes Degree of protection IP66

NEMA 13

NEMA 4X

NEMA 4 Mounting Method Horizontal

Bracket

Floor Mounting position As required Product Category Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Tube length 100 mm Type Base module

Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

ETIM for 171311 Low-voltage industrial controls and switchgear (EC001152)

Feature Name

Feature Value

Connection type auxiliary circuit (EF006820)

Spring clamp connection

Suitable for tube mounting (EF001668)

No

Suitable for angle mounting (EF001669)

Yes

Suitable for floor mounting (EF025108)

Yes

Colour (EF000007)

Other

Suitable for AS interface (EF005768)

No

Suitable for M12...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-SWD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.