

INDUSTRIAL COMPONENT DATA

SL4-PIB-FW 171303 Y7-171303 EATON ELECTRIC Base module for vertical mounting on one sides

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-PIB-FW



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-PIB-FW
Catalog number	Y7-171303
Category	Connection module for signal tower
Minimum order	1 Pcs
Document ID	EO-E64785AC52
Generated	2026-08-03

Product Overview

Base module;for vertical mounting on one sides

SL4-PIB-FW

Eaton Moeller® series SL4 Base module, for vertical mounting on one sides

Base module, Color black, Product range: SL signal towers, Connection technique: Push in terminals, Mounting type: for vertical mounting, Fitted with: One-sided base with bracket, including cover, Number of modules: max. 5 modules, For use with: SL4-L-..., SL4-BL-..., SL4-FL-..., SL4-AP-..., Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, IEC degree of protection: IP66, IEC/EN 60529, Protection type UL: Type 4, 4X, 13

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Base module Catalog Number 171303 Model Code SL4-PIB-FW EAN 4015081678457 Product Length/Depth 56 mm Product Height 94 mm Product Width 66 mm Product Weight 0.067 kg

Certifications UL report applies to both US and Canada

CSA Class No.: NKCR7

CSA-C22.2 No. 14-10

IEC/EN 60947-5-1

IEC/EN 60529

UL File No.: E29184

CE

UL

Certified by UL for use in Canada

UL 508

UL Category Control No.: NKCR

CSA-C22.2 No. 94-91 Features & Functions

Color Other Fitted with: Cover

Bracket Number of modules Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base)

Max. 5 General

Connection to SmartWire-DT No Degree of protection NEMA 13

NEMA 4X

IP66

NEMA 4 Mounting Method Bracket

Floor

Vertical Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Base module Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (AWG) 24 - 16 Terminal capacity (flexible with ferrule and plastic collar) 0.25 - 0.75 mm² Terminal capacity (solid/flexible) 0.2 - 1.5 mm² Terminal capacity (solid/flexible with ferru...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-PIB-FW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.