

INDUSTRIAL COMPONENT DATA

U-CI43 065028 Y7-65028 EATON ELECTRIC Base, HxWxD 250x375x120mm

Brand: EATON - MOELLER | Manufacturer Part Number: U-CI43



Manufacturer	EATON - MOELLER
MPN / Reference	U-CI43
Catalog number	Y7-65028
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-0F8A41F3AF
Generated	2026-08-06

Product Overview

Base, HxWxD=250x375x120mm

Eaton xEnergy Safety Ci LV systems LV switchgear. Base, HxWxD=250x375x120mm

Panel enclosure base, material characteristic polycarbonate, impact-resistant, enclosure side plates closed, knockout, open top and bottom, RAL 7035, extensive accessories for distribution board assembly is separately available

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Insulating Enclosures**

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci empty enclosure base Catalog Number 065028 Model Code U-CI43 EAN 4015080650287 Product Length/Depth 150 mm Product Height 250 mm Product Width 375 mm Product Weight 1.168 kg

Compliances RoHS conform Certifications EN 61439-2

EN 62208 Product specifications

Special features Flanges ?#024355Distance frame for CI45... ?#110103Sides closed, but with full area knockoutOpen tip and bottom Type Basic enclosureEnclosure basesxEnergy Safety Ci Features Cover with overpressure release 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. 10.13 Mechanical function Meets the product standard's requirements. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product

standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects 960 °C 10.2.4 Resistance to ultra-violet (UV) radiation Not relevant to indoor installations. 10.2.5 Lifting 10 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / U-CI43 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.