

INDUSTRIAL COMPONENT DATA

U-CI44E 069642 Y7-69642 EATON ELECTRIC Base, individual enclosure, HxWxD 375x375x120mm

Brand: EATON - MOELLER | Manufacturer Part Number: U-CI44E



Manufacturer	EATON - MOELLER
MPN / Reference	U-CI44E
Catalog number	Y7-69642
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-45D2A4D8B2
Generated	2026-08-05

Product Overview

Base, individual enclosure, HxWxD=375x375x120mm

Individual Box Base CI HxWxD=375x375x120mm

Eaton xEnergy Safety Ci LV systems LV switchgear. Base, individual enclosure, HxWxD=375x375x120mm

Individual enclosure base E, material characteristic polycarbonate, impact-resistant, metric cable entry knockouts in all sides, knockout, cable entries top and bottom, each=1xM50/32 and 2xM40/25 and 8xM25/16 and 2xM20, each side=1xM63/40 and 6xM25/16 and 10xM20 and 2xM16, RAL 7035, direct mounting to the wall possible without further accessories

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci empty enclosure base Catalog Number 069642 Model Code U-CI44E EAN 4015080696421 Product Length/Depth 150 mm Product Height 375 mm Product Width 375 mm Product Weight 3.757 kg Complies RoHS conform Certifications EN 61439-2

EN 62208 Product specifications

Special features Flanges ?#024355Distance frame for CI45... ?#110103Metric cable entry knockouts in all sidesFull-area knockouts in the sides Type Basic enclosureEnclosure basesxEnergy Safety Ci Features Cover with overpressure release 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. 10.12 Electromagnetic

compatibility Is the panel builder's responsibility. 10.13 Mechanical function Meets the product standard's requirements. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects 960 °C 10.2.4 Resistance to ultra-violet (UV) radiation Not relevant to indoor installations. 10.2.5 Lifting 20 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest appl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / U-CI44E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.