

INDUSTRIAL COMPONENT DATA

XN-S3S-SBC 140090 Y7-140090 EATON ELECTRIC Base module washer XI/ON, screw, 3 connection levels, con. to C r..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-S3S-SBC



Manufacturer	EATON - MOELLER
MPN / Reference	XN-S3S-SBC
Catalog number	Y7-140090
Category	Fieldbus, decentr. periphery - mounting frame
Minimum order	1 Pcs
Document ID	EO-EA4DBB9ADE
Generated	2026-08-05

Product Overview

Base module washer XI/ON, screw, 3 connection levels, con. to C rail

XN-S3S-SBC

Rack, XI/ON slice card base modules, Connection levels: 3 connection levels, Connection technique: Screw terminals, for Slice module, Connection to C rail, Degree of Protection: IP20, For use with: XN-2DO-24VDC-0.5A-P, XN-2DO-24VDC-0.5A-N, XN-2DO-24VDC-2A-P, XN-2DO-120/230VAC-0.5A, Standards: EN 61000-6-2, EN 61000-6-4, EN 61131-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Remote I / O Modules XION**

Additional Product Information

General specifications

Product Name Eaton XN Rack Catalog Number 140090 Model Code XN-S3S-SBC EAN 7640130121140 Product Length/Depth 117.6 mm Product Height 49.9 mm Product Width 12.6 mm Product Weight 0.041 kg Certifications CE Certified by UL for use in Canada

IEC/EN 61000-6-2

UL File No.: E205091

IEC/EN 61000-6-4

CSA Class No.: 2252-01, 2252-81

UL Recognized

IEC/EN 61131-2

CE, cUL

UL 508

UL report applies to both US and Canada

IEC/EN 6113-2

Rated data for terminations according to IEC/EN 60947-7-1

UL Category Control No.: NRAQ, NRAQ7

CSA-C22.2 No. 142 Features & Functions

Fitted with: Pluggable modules, digital I/O

Pluggable modules, central modules

Power supply General

Degree of protection IP20 Mounting method Rail mounting possible Number of connection levels 3 Type XI/ON slice card base module Used with XN-2DO-24VDC-0.5A-N

XN-2DO-24VDC-0.5A-P

XN-2DO-24VDC-2A-P

XN-2DO-120/230VAC-0.5A Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Continuous according to IEC/EN 60068-2-29

Mechanical, According to IEC/EN 60068-2-27 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Environmental conditions Harmful gasses - H2S: 1 ppm (relative humidity < 75%, no condensation)

Harmful gasses - SO2: 10 ppm (relative humidity < 75%, no condensation) Relative humidity 5 - 95 % (i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-S3S-SBC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.