

INDUSTRIAL COMPONENT DATA

XN-S3S-SBB 140088 Y7-140088 EATON ELECTRIC Base module washer XI/ON, screw, 3 connection levels

Brand: EATON - MOELLER | Manufacturer Part Number: XN-S3S-SBB



Manufacturer	EATON - MOELLER
MPN / Reference	XN-S3S-SBB
Catalog number	Y7-140088
Category	Fieldbus, decentr. periphery - mounting frame
Minimum order	1 Pcs
Document ID	EO-D9BD8381E0
Generated	2026-08-04

Product Overview

Base module washer XI/ON, screw, 3 connection levels

XN-S3S-SBB

Rack, XI/ON slice card base modules, Connection levels: 3 connection levels, Connection technique: Screw terminals, for Slice module, Degree of Protection: IP20, For use with: XN-2DI-24VDC-P, XN-2DI-24VDC-N, XN-2DI-120/230VAC, XN-1AI-I(0/4...20MA), XN-2AI-I(0/4...20MA), XN-1AI-U(-10/0...+10VDC), XN-2AI-U(-10/0...+10VDC), XN-2AI-PT/NI-2/3, XN-1AO-I(0/4...20MA), XN-2AO-I(0/4...20MA), XN-2AO-U(-10/0...+10VDC), Standards: EN 61000-6-2, EN 61000-6-4, EN 61131-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications

Product Name Eaton XN Rack Catalog Number 140088 Model Code XN-S3S-SBB EAN 7640130121133 Product Length/Depth 117.6 mm Product Height 49.9 mm Product Width 12.6 mm Product Weight 0.041 kg Certifications IEC/EN 61131-2

UL 508

CE, cUL

CE

IEC/EN 61000-6-2

UL File No.: E205091

Rated data for terminations according to IEC/EN 60947-7-1

UL Category Control No.: NRAQ, NRAQ7

UL Recognized

IEC/EN 6113-2

Certified by UL for use in Canada

CSA-C22.2 No. 142

UL report applies to both US and Canada

IEC/EN 61000-6-4

CSA Class No.: 2252-01, 2252-81 Features & Functions

Fitted with: Pluggable modules, digital I/O

Pluggable modules, central modules

Power supply

Pluggable modules, analog I/O General

Degree of protection IP20 Mounting method Rail mounting possible Number of connection levels 3 Type XI/ON slice card base module Used with XN-1AI-U (-10 - 10 V DC)

XN-2DI-24VDC-P

XN-2DI-120/230VAC

XN-1AI-I(0 - 20 mA)

XN-2AI-PT/NI-2/3

XN-2AI-U (-10 - 10 V DC)

XN-1AO-I(0 - 20 mA)

XN-2AI-I(0 - 20 mA)

XN-2AO-I(0 - 20 mA)

XN-2AO-U (-10 - 10 V DC)

XN-2DI-24VDC-N Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical, According to IEC/EN 60068-2-27

Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Environmental conditions Har...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-S3S-SBB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.