

INDUSTRIAL COMPONENT DATA

U-CI45X 098470 Y7-98470 EATON ELECTRIC Base, smooth sides, HxWxD 500x375x120mm

Brand: EATON - MOELLER | Manufacturer Part Number: U-CI45X



Manufacturer	EATON - MOELLER
MPN / Reference	U-CI45X
Catalog number	Y7-98470
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-F0D4A8DAE6
Generated	2026-08-06

Product Overview

Base, smooth sides, HxWxD=500x375x120mm

Individual enclosure base x, material characteristic polycarbonate, impact-resistant, smooth sides, without knockouts, for any drilling dimensions, wall thickness=6.5mm, RAL 7035, direct mounting to the wall possible without further accessories

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

Base, smooth sides, HxWxD=500x375x120mm Individual enclosure base x, material characteristic polycarbonate, impact-resistant, smooth sides, without knockouts, for any drilling dimensions, wall thickness=6.5mm, RAL 7035, direct mounting to the wall possible without further accessories

General specifications
Product name Eaton xEffect Ci Enclosures Switch- & Controlgear Enclosure
Part no. U-CI45XEAN4015080984702
Product Length/Depth 120 millimetre
Product height 500 millimetre
Product width 375 millimetre
Product weight 5.1 kilogram
Compliances RoHS conform
Certifications IEC 60947

VDE

UL 508

EN 60947-3

CSA Std. C22.2 No. 14-05

EN 62208

EN 61439-2
Product Tradename xEffect Ci
Product Type Enclosures
Product Sub Type Switch- & Controlgear
Enclosure
Delivery program Type Basic enclosure

Enclosure bases

xEnergy Safety CiAccessory/spare part typeIndividual enclosure bottomsColorGrayNominal current1600 ATechnical Data - ElectricalCircuit integrityOtherTechnical Data - MechanicalUnit typeModular systemBase typePlainSurface protectionOtherEnclosure materialPlasticWidth in number of modular spacings17Mounting methodSurface mounted (plaster)Degree of protectionIK10

Other

IP65Number of conduit inlets0Number of modules1Number of openings (flange plates)0Number of rows0Built-in depth200 mmInternal depth100 mmCable entry typeTop and bottom

Drill as required

TransverseCover/door modelClosedCover/door typeOptional

NonePlate thickness (cabinet)9 mmPlate thickness (cover/door)6 mmTemperature-rise verification as per IE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / U-CI45X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.