

INDUSTRIAL COMPONENT DATA

SL7-CB-EMH 171449 Y7-171449 EATON ELECTRIC Base with external fastening holes

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-CB-EMH



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-CB-EMH
Catalog number	Y7-171449
Category	Connection module for signal tower
Minimum order	1 Pcs
Document ID	EO-0D027A79E9
Generated	2026-08-05

Product Overview

Base with external fastening holes

SL7-CB-EMH

Eaton Moeller® series SL7 Base module;external fixing holes

Base module, Color black, Product range: SL signal towers, Connection technique: Spring-loaded terminals, Mounting type: for horizontal mounting, Fitted with: Base with external fixing holes, including cover, Number of modules: max. 5 modules, For use with: SL7-L-..., SL7-BL-..., SL7-FL-..., SL7-AP-..., Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, IEC degree of protection: IP66, IEC/EN 60529, Protection type UL: Type 4, 4X, 13

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Base module Catalog Number 171449 Model Code SL7-CB-EMH EAN

4015081677795 Product Length/Depth 100 mm Product Height 94 mm Product Width 100 mm Product Weight 0.176 kg

Certifications UL 508

IEC/EN 60947-5-1

Certified by UL for use in Canada

CSA-C22.2 No. 14-10

IEC/EN 60529

UL Category Control No.: NKCR

UL report applies to both US and Canada

CSA-C22.2 No. 94-91

CE

UL File No.: E29184

CSA Class No.: NKCR7

UL Features & Functions

Color Other Fitted with: Cover

External fixing holes Number of modules Max. 10 (with base for mounting on both sides)

Max. 5

Max. 5 (with standard base) General

Connection to SmartWire-DT No Degree of protection IP66

NEMA 4X

NEMA 13

NEMA 4 Mounting Method Bracket

Horizontal

Floor Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Base module Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity (AWG) 24 - 14 Terminal capacity (flexible with ferrule and plastic collar) 0.25 - 1.5 mm² Terminal capacity (solid/flexible) 0.13 - 2.5 mm² Electrical rating

Rated in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-CB-EMH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.