

**INDUSTRIAL COMPONENT DATA**

# SL4-PIB-IMH 171300 Y7-171300 EATON ELECTRIC Base with internal fastening holes

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-PIB-IMH



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | SL4-PIB-IMH                        |
| Catalog number  | Y7-171300                          |
| Category        | Connection module for signal tower |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-545AF993F3                      |
| Generated       | 2026-08-06                         |

## Product Overview

Base with internal fastening holes

SL4-PIB-IMH

Eaton Moeller® series SL4 Base module;internal fixing holes

Base module, Color black, Product range: SL signal towers, Connection technique: Push in terminals, Mounting type: for horizontal mounting, Fitted with: Base with internal (on the inside) fixing holes, including cover, Number of modules: max. 5 modules, For use with: SL4-L-..., SL4-BL-..., SL4-FL-..., SL4-AP-..., Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, IEC degree of protection: IP66, IEC/EN 60529, Protection type UL: Type 1

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Base module Catalog Number 171300 Model Code SL4-PIB-IMH EAN 4015081679188 Product Length/Depth 43 mm Product Height 71 mm Product Width 43 mm Product Weight 0.055 kg

Certifications CSA-C22.2 No. 94-91

IEC/EN 60529

Certified by UL for use in Canada

UL 508

CE

CSA Class No.: NKCR7

IEC/EN 60947-5-1

CSA-C22.2 No. 14-10

UL

UL report applies to both US and Canada

UL Category Control No.: NKCR

UL File No.: E29184 Features & Functions

Color Other Fitted with: Cover

Internal (on the inside) fixing holes Number of modules Max. 10 (with base for mounting on both sides)

Max. 5

Max. 5 (with standard base) General

Connection to SmartWire-DT No Degree of protection IP66

NEMA 1 Mounting Method Floor

Horizontal

Bracket Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Base module Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity (AWG) 24 - 16 Terminal capacity (flexible with ferrule and plastic collar) 0.25 - 0.75 mm<sup>2</sup> Terminal capacity (solid/flexible) 0.2 - 1.5 mm<sup>2</sup> Terminal capacity (solid/fl...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-PIB-IMH with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.