

INDUSTRIAL COMPONENT DATA

SL4-PIB-IMS 171301 Y7-171301 EATON ELECTRIC Base with internal fixing screw

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-PIB-IMS



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-PIB-IMS
Catalog number	Y7-171301
Category	Connection module for signal tower
Minimum order	1 Pcs
Document ID	EO-350DA4973C
Generated	2026-08-04

Product Overview

Base with internal fixing screw

SL4-PIB-IMS

Eaton Moeller® series SL4 Base module;internal fixing screw

Base module, Color black, Product range: SL signal towers, Connection technique: Push in terminals, Mounting type: for horizontal mounting, Fitted with: Base with built-in (pre-assembled) fixing screws, including cover, Number of modules: max. 5 modules, For use with: SL4-L-..., SL4-BL-..., SL4-FL-..., SL4-AP-..., Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, IEC degree of protection: IP66, IEC/EN 60529, Protection type UL: Type 4, 4X, 13

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Base module Catalog Number 171301 Model Code SL4-PIB-IMS EAN 4015081678433 Product Length/Depth 43 mm Product Height 91 mm Product Width 43 mm Product Weight 0.061 kg
Compliances CE Marked Certifications UL 508

UL Listed

CSA Certified

cULus Listed

UL Listed file E29184

CSA Std. C22.2 No. 14-10

CSA Std. C22.2 No. 94-91

CSA Class No. NKCR7

IEC Rated

UL File No.: E29184

CSA-C22.2 No. 14-10

Certified by UL for use in Canada

CSA-C22.2 No. 94-91

UL Category Control No.: NKCR

UL

CE

UL report applies to both US and Canada

CSA Class No.: NKCR7

IEC/EN 60529

IEC/EN 60947-5-1 Catalog Notes 0 Features & Functions

Color Other Fitted with: Cover

Built-in (pre-assembled) fixing screws Number of modules Max. 5 (with standard base)

Max. 5

Max. 10 (with base for mounting on both sides) General

Accessories Built-in fixing screws Connection to SmartWire-DT No Degree of protection IP66

NEMA 4

NEMA 4X

NEMA 13 Mounting Method Horizontal

Floor

Bracket Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Base module Used with Used with SL4-L, SL4-BL, SL4-FL, SL4-AP Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Da...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-PIB-IMS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.