

INDUSTRIAL COMPONENT DATA

BB-UL-18/3P-3M/57 121983 Y7-121983 EATON ELECTRIC

Phase busbar, 3-phase, 18qmm, pin, 1m

Brand: EATON - MOELLER | Manufacturer Part Number: BB-UL-18/3P-3M/57



Manufacturer	EATON - MOELLER
MPN / Reference	BB-UL-18/3P-3M/57
Catalog number	Y7-121983
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-C728EB049F
Generated	2026-08-05

Product Overview

Phase busbar, 3-phase, 18qmm, pin, 1m

BB-UL-18/3P-3M/57

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Phase busbar, 3-phase, 18qmm, pin, 1m Block busbar for FAZ, type conforms to UL508, EN/IEC 60947-2 Delivery program Basic function Busbar Basic function accessories Busbar for miniature circuit-breaker Application Switchgear for industrial and advanced commercial applications Busbar type Three-phase Product range BB-UL Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 80 A Heat dissipation per pole, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -5 °C Operating ambient temperature max. +100 °C Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215) Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar ( [ACN992011]) Number of phases 3 Number of poles 57 Suitable for number of devices 57 Pitch dimensions 0 mm Cross section 18 mm² Length 1000 mm Number of modular spacings 57 Rated permanent current Iu 80 A Type of electric connection Pin Insulated Yes Rated surge voltage 10 kV Conditioned rated short-circuit current Iq 10 kA Max. rated operation voltage Ue 277 V Rated short-time withstand current Icw 0 kA Suitable for devices with N-busbar No Suitable for devices with auxiliary switch No Characteristics

Characteristic curve

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB-UL-18/3P-3M/57 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.