

INDUSTRIAL COMPONENT DATA

**BB-UL-25/2P+AS-2,5M/46 121995 Y7-121995 EATON
ELECTRIC Phase busbar, 2-phase, 25qmm, pin, 1m**

Brand: EATON - MOELLER | Manufacturer Part Number: BB-UL-25/2P+AS-2,5M/46



Manufacturer	EATON - MOELLER
MPN / Reference	BB-UL-25/2P+AS-2,5M/46
Catalog number	Y7-121995
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-C07D17D9F0
Generated	2026-08-02

Product Overview

Phase busbar, 2-phase, 25qmm, pin, 1m

BB-UL-25/2P+AS-2,5M/46

Block busbar for FAZ, type conforms to UL508, EN/IEC 60947-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 121995 Model Code BB-UL-25/2P+AS-2,5M/46 EAN

4015081201952 Product Length/Depth 1009 mm Product Height 37 mm Product Width 22 mm Product Weight 0.727 kg

Compliances RoHS conform Certifications UL 508 Product specifications

Used with Busbar

BB-UL Type Features Insulated Accessory/spare part type Busbar for miniature circuit breaker Electric connection type Pin
Rated operational current for specified heat dissipation (In) 100 A Rated surge voltage 10 KV Rated uninterrupted current
(Iu) 100 A Static heat dissipation, non-current-dependent 0 W Suitable for number of devices 46 Application Switchgear for
industrial and advanced commercial applications Number of poles Forty-six-pole Color Other Rated short-time withstand
current (Icw) 0 kA Ambient operating temperature - max 100 °C Ambient operating temperature - min -5 °C Cross section
25 mm² Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of modular spacings 46
Number of phases 2 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 277 V Rated conditional short-circuit
current (Iq) 10 kA Functions Busbar Suitable for 46 devices

ETIM for 121995 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

2

Number of poles (EF001391)

46

Suitable for number of devices (EF007241)

46

Module width (EF007504)

0 mm

Cross section (EF000649)

25 mm²

Length (EF001438)

100...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB-UL-25/2P+AS-2,5M/46 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.