

INDUSTRIAL COMPONENT DATA

BB-UL-25/3P-4,5M/39 121994 Y7-121994 EATON ELECTRIC
Phase busbar, 3-phase, 25qmm, pin, 1m

Brand: EATON - MOELLER | Manufacturer Part Number: BB-UL-25/3P-4,5M/39



Manufacturer	EATON - MOELLER
MPN / Reference	BB-UL-25/3P-4,5M/39
Catalog number	Y7-121994
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-D9DB3BF9E4
Generated	2026-08-03

Product Overview

Phase busbar, 3-phase, 25qmm, pin, 1m

BB-UL-25/3P-4,5M/39

Block busbar for FAZ, type conforms to UL508, EN/IEC 60947-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 121994 Model Code BB-UL-25/3P-4,5M/39 EAN 4015081201945

Product Length/Depth 1040 mm Product Height 37 mm Product Width 22 mm Product Weight 0.915 kg Compliances RoHS conform Product specifications

Used with Busbar

BB-UL Type Features Insulated

Can be cut to size Accessory/spare part type Busbar for miniature circuit breaker Electric connection type Pin Rated operational current for specified heat dissipation (In) 100 A Rated surge voltage 10 KV Rated uninterrupted current (Iu) 100 A Static heat dissipation, non-current-dependent 0 W Suitable for number of devices 0 Application Switchgear for industrial and advanced commercial applications Number of poles Thirty-nine-pole Color Other Rated short-time withstand current (Icw) 0 kA Ambient operating temperature - max 100 °C Ambient operating temperature - min -5 °C Cross section 25 mm² Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of modular spacings 39 Number of phases 3 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 277 V Rated conditional short-circuit current (Iq) 10

kA Functions Busbar Suitable for 39 devices

ETIM for 121994 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of poles (EF001391)

39

Suitable for number of devices (EF007241)

0

Module width (EF007504)

0 mm

Cross section (EF000649)

25 mm²

Length (EF001438)

1040 mm

C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB-UL-25/3P-4,5M/39 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.