

INDUSTRIAL COMPONENT DATA

BB1P100M12 EATON ELECTRIC BUSBAR, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 208 mm, 12P, UL

Brand: EATON - MOELLER | Manufacturer Part Number: BB1P100M12



Manufacturer	EATON - MOELLER
MPN / Reference	BB1P100M12
Catalog number	10000
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-F2DC67564D
Generated	2026-08-03

Product Overview

Sngl-phase 1000v DC BB, 100A, 12 pins EC

Sngl-phase 1000v DC BB, 100A, 12 pins EC - Busbar, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 208 mm, 12P, UL, single phase 12-way comb-type busbar, with end stop

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Busbar, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 208 mm, 12P, UL, single phase 12-way comb-type busbar, with end stop
Fuse accessory, BUSBAR, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 208 mm, 12P, UL, single phase 12-way comb-type busbar, with end stop, UL 508
Delivery program

Product rangeFuse accessoryField of applicationlow voltageRated current [I]_N100 ARated voltageAC 600 V

DC 1000 VSize15 x 16 x 208 mmDescriptionsingle phase 12-way comb-type busbar

with end stopNumber of poles12PStandard/ApprovalULStandards/RegulationsUL 508Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar

( [ACN992011])Number of phases1Number of poles12Suitable for number of devices12Pitch

dimensions17.8 mmCross section25 mm²Length208 mmNumber of modular spacings12Rated permanent current I_u100AType of electric connectionForkInsulatedYesRated surge voltageU_ckVConditioned rated short-circuit current I_q10 kAMax. rated operation voltage U_e600 VRated short-time withstand current I_{cw}10 kASuitable for devices with N-busbarNoSuitable for devices with auxiliary switchNo

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB1P100M12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.