

INDUSTRIAL COMPONENT DATA

BB1P100M15 EATON ELECTRIC BUSBAR, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 208 mm, 12P, UL

Brand: EATON - MOELLER | Manufacturer Part Number: BB1P100M15



Manufacturer	EATON - MOELLER
MPN / Reference	BB1P100M15
Catalog number	10000
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-A685402638
Generated	2026-08-05

Product Overview

Sngl-phase 1000v DC BB, 100A, 15 pins EC

Sngl-phase 1000v DC BB, 100A, 15 pins EC - Busbar, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 272 mm, 15P, UL, single phase 15-way comb-type busbar, with end cap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Busbar, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 272 mm, 15P, UL, single phase 15-way comb-type busbar, with end cap
Fuse accessory, BUSBAR, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 272 mm, 15P, UL, single phase 15-way comb-type busbar, with end cap, UL 508
Delivery program

Product range Fuse accessory Field of application low voltage Rated current [I]_N 100 A Rated voltage AC 600 V

DC 1000 V Size 15 x 16 x 272 mm Descriptions single phase 15-way comb-type busbar

with end cap Number of poles 15P Standard/Approval UL Standards/Regulations UL 508 Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215) Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar

( [ACN992011]) Number of phases 1 Number of poles 15 Suitable for number of devices 15 Pitch

dimensions 17.8 mm Cross section 25 mm² Length 272 mm Number of modular spacings 15 Rated permanent current I_u 100A Type of electric connection Fork Insulated Yes Rated surge voltage kV Conditioned rated short-circuit current I_q 10 kA Max.rated operation voltage U_e 600 V Rated short-time withstand current I_{cw} 10 kA Suitable for devices with N-busbar No Suitable for devices with auxiliary switch No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB1P100M15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.