

INDUSTRIAL COMPONENT DATA

BB1P100M57 EATON ELECTRIC Sngl-phs 1000v DC BB, 100A, 57 pin NO EC

Brand: EATON - MOELLER | Manufacturer Part Number: BB1P100M57



Manufacturer	EATON - MOELLER
MPN / Reference	BB1P100M57
Catalog number	10000
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-6E97A25020
Generated	2026-08-05

Product Overview

Sngl-phs 1000v DC BB, 100A, 57 pin NO EC

Sngl-phs 1000v DC BB, 100A, 57 pin NO EC - Busbar, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 1012 mm, 57P, UL, single phase 57-way comb-type busbar, without end stop

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Busbar, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 1012 mm, 57P, UL, single phase 57-way comb-type busbar, without end stop
Fuse accessory, BUSBAR, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 1012 mm, 57P, UL, single phase 57-way comb-type busbar, without end stop, UL 508, can be cut to length
Delivery program

Product range Fuse accessory
Field of application low voltage
Functionality can be cut to length
Rated current [I]_N 100 A
Rated voltage AC 600 V

DC 1000 V
Size 15 x 16 x 1012 mm
Description single phase 57-way comb-type busbarwithout end stop
Number of poles 57P
Standard/Approval UL Standards/Regulations UL 508
Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar

( [ACN992011])
Number of phases 1
Number of poles 57
Suitable for number of devices 57
Pitchdimensions 17.8 mm
Cross section 25 mm²
Length 1012 mm
Number of modular spacings 57
Rated permanent current I_N 100 AType of electric connection Fork
Insulated Yes
Rated surge voltage kV
Conditioned rated short-circuit current I_q 10 kA
Max.rated operation voltage U_e 600 V
Rated short-time withstand current I_{cw} 10 kA
Suitable for devices with N-busbar No
Suitable

for devices with auxiliary switchNo

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB1P100M57 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.