

INDUSTRIAL COMPONENT DATA

BB3P100M15 EATON ELECTRIC BUSBAR, low voltage, 100 A, AC 600 V, DC 1000 V, 15 x 16 x 208 mm, 12P, UL

Brand: EATON - MOELLER | Manufacturer Part Number: BB3P100M15



Manufacturer	EATON - MOELLER
MPN / Reference	BB3P100M15
Catalog number	10000
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-F6D893FA72
Generated	2026-08-03

Product Overview

Three phase bb,100A,15 pins,assembled EC

Three phase bb,100A,15 pins,assembled EC - Busbar, low voltage, 100 A, AC 600 V, DC 600 V, 22 x 37 x 266 mm, 15P, UL, three phase 5-way comb-type busbar, with end cap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Busbar, low voltage, 100 A, AC 600 V, DC 600 V, 22 x 37 x 266 mm, 15P, UL, three phase 5-way comb-type busbar, with end cap
Fuse accessory, BUSBAR, low voltage, 100 A, AC 600 V, DC 600 V, 22 x 37 x 266 mm, 15P, UL, three phase 5-way comb-type busbar, with end cap, UL 508
Delivery program

Product range Fuse accessory
Field of application low voltage
Rated current [I]_N 100 A
Rated voltage AC 600 V

DC 600 V
Size 22 x 37 x 266 mm
Description three phase 5-way comb-type busbar

with end cap
Number of poles 15P
Standard/Approval UL
Standards/Regulations UL 508
Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar ( [ACN992011])
Number of phases 3
Number of poles 15
Suitable for number of devices 15
Pitch

dimensions 17.8 mm
Cross section 25 mm²
Length 266 mm
Number of modular spacings 15
Rated permanent current I_u 100 A

Type of electric connection Fork
Insulated Yes
Rated surge voltage kV
Conditioned rated short-circuit current I_q 10 kA
Max. rated operation voltage U_e 600 V
Rated short-time withstand current I_{cw} 10 kA
Suitable for devices with N-busbar No
Suitable for devices with auxiliary switch No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB3P100M15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.