

INDUSTRIAL COMPONENT DATA

BB3P100M57 EATON ELECTRIC BUSBAR, low voltage, 100 A, AC 600 V, DC 600 V, 23 x 37 x 1009 mm, 57P, UL

Brand: EATON - MOELLER | Manufacturer Part Number: BB3P100M57



Manufacturer	EATON - MOELLER
MPN / Reference	BB3P100M57
Catalog number	10000
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-CBCFB258E1
Generated	2026-08-04

Product Overview

Three phase bb,100A, 57 pins, w/o endcap

Three phase bb,100A, 57 pins, w/o endcap - Busbar, low voltage, 100 A, AC 600 V, DC 600 V, 23 x 37 x 1009 mm, 57P, UL, three phase 19-way comb-type busbar, without end stop

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Busbar, low voltage, 100 A, AC 600 V, DC 600 V, 23 x 37 x 1009 mm, 57P, UL, three phase 19-way comb-type busbar, without end stop Fuse accessory, BUSBAR, low voltage, 100 A, AC 600 V, DC 600 V, 23 x 37 x 1009 mm, 57P, UL, three phase 19-way comb-type busbar, without end stop, UL 508, can be cut to length Delivery program

Product range Fuse accessory Field of application low voltage Functionality can be cut to length Rated current [I] 100 A Rated voltage AC 600 V

DC 600 V Size 23 x 37 x 1009 mm Description three phase 19-way comb-type busbar

without end stop Number of poles 57 P Standard/Approval UL Standards/Regulations UL 508 Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215) Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar

( [ACN992011]) Number of phases 3 Number of poles 57 Suitable for number of devices 57 Pitch

dimensions 17.8 mm Cross section 25 mm² Length 1009 mm Number of modular spacings 57 Rated permanent current I_u 100

A Type of electric connection Fork Insulated Yes Rated surge voltage kV Conditioned rated short-circuit current I_q 10 kA Max.

rated operation voltage U_e 600 V Rated short-time withstand current I_{cw} 10 kA Suitable for devices with N-busbar No Suitable

for devices with auxiliary switchNo

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BB3P100M57 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.