

INDUSTRIAL COMPONENT DATA

BBA-TP3/100-C 138373 Y7-138373 EATON ELECTRIC

Connection terminal board 3, 35-150mm², 90mm, compact

Brand: EATON - MOELLER | Manufacturer Part Number: BBA-TP3/100-C



Manufacturer	EATON - MOELLER
MPN / Reference	BBA-TP3/100-C
Catalog number	Y7-138373
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-8CB64BC3EE
Generated	2026-08-04

Product Overview

Connection terminal board 3, 35-150mm², 90mm, compact

BBA-TP3/100-C

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Connection terminal board 3, 35-150mm², 90mm, compact

Connection terminal board, 60-mm compact system, poles=3, screw terminals, terminal capacity=35 up to 150mm² or AWG2-MCM300 or 10x20x1 or 10x16x0.8, I_e=480A, width=90mm, can be used for rail 12x5/10, silicon free, chlorine free, self-extinguishing to UL 94, track resistance CTI 200, temperature resistant to 120 °C, the terminal can be removed for the connection of uncut conductors, passing through is not possible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure Catalog Number 138373 Model Code BBA-TP3/100-C EAN 4015081351534 Product Length/Depth 90 mm Product Height 160 mm Product Width 115 mm

Product Weight 0.575 kg Compliances RoHS conform Delivery program

Type Technical data - electrical

Rated operation current (I_e) 480 A Rated operational current 480 A Rated operational current (I_e) - max 480 A Technical data - mechanical

Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar width - min 12 mm Busbar width - max 30 mm

Terminal capacity (conductor) 20 mm x 1 mm (10x)

35 mm² - 150 mm²

AWG 2 - MCM 300 Conductor cross section - max 150 mm² Width clamp 90 mm Additional information

Functions Clamp plate

Connections Special features The terminal can be removed for the connection of uncut conductors

A cable block is used to connect the conductor to the busbar

Suitable for Three-pole

Flat rail

Sector conductor connection

Round conductor connection

Strip conductor connection Used with 12 mm x 5/10 mm rail

Compact system

Connection

ETIM for 138373 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

5 mm

Busbar width (EF007219)

12 mm

Suitable for (EF000073)

Flat rail

Width clamp (EF007092)

90 mm

Max. conductor cross section (EF004969)

150 mm²

Max. rated operation current I_e (EF007356)

480 A

Suitable for round conductor connection (EF007258)

Yes

Suitable for sector conduc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA-TP3/100-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.