

INDUSTRIAL COMPONENT DATA

BBA-TP3/1000 107207 Y7-107207 EATON ELECTRIC Terminal plate, 3p, 1000mm², 1600A

Brand: EATON - MOELLER | Manufacturer Part Number: BBA-TP3/1000



Manufacturer	EATON - MOELLER
MPN / Reference	BBA-TP3/1000
Catalog number	Y7-107207
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-B0F985A845
Generated	2026-08-04

Product OverviewTerminal plate, 3p, 1000mm², 1600A

BBA-TP3/1000

Eaton xEffect SASy 60i Enclosures Switch- & Controlgear Enclosure. Terminal plate, 3p, 1000mm², 1600A

Connection kit, 60 mm system, poles=3, terminal capacity=Up to (2 x) 10x50x1 and (2 x) 50x10, I_e=1600A, width=228mm, can be used for rail 30x10 and double T profile, termination space WxH=5x28, silicon free, chlorine free, self-extinguishing to UL 94, track resistance CTI 200, temperature resistant to 120 °C, adapted to Eaton NZM4, fixing direct over busbar terminals, passing through is not possible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASy 60i terminal plate Catalog Number 107207 Model Code BBA-TP3/1000 EAN

4015081069705 Product Length/Depth 90 mm Product Height 204 mm Product Width 228 mm Product Weight 1.873 kg

Compliances RoHS conform Delivery program

Type Technical data - electrical

Rated operation current (I_e) 1600 A Rated operational current 1600 A Rated operational current (I_e) - max 1600 A

Creepage resistance CTI 200 Technical data - mechanical

Material Silicon free, chlorine free Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar width - min 12 mm

Busbar width - max 30 mm Terminal contact area 5 mm x 28 mm Terminal capacity (conductor) 50 mm x 10 mm (2x)

10 segments of 50 mm x 1 mm (2x) Conductor cross section - max 1000 mm² Width clamp 228 mm Design verification as per IEC/EN 61439 - technical data

Temperature resistance Temperature resistant to 120 °C Additional information

Features Self-extinguishing acc. UL 94 Functions Connection kit

Connections Special features Adapted to Eaton NZM4

Fixing direct over busbar terminals

Looping is possible

Suitable for Flat rail

Three-pole

Round conductor connection

Sector conductor connection

Strip conductor connection Used with 30 mm x 10 mm rail

Double T profile

60 mm system

Connection

ETIM for 107207 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

5 mm

Busbar width (EF007219)

12 mm

Suitable for (EF000073)

Flat rail

Width clamp (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA-TP3/1000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.