

INDUSTRIAL COMPONENT DATA

BBA-TP4/300 138385 Y7-138385 EATON ELECTRIC Incoming set, 4p, 560A, to 300mm²

Brand: EATON - MOELLER | Manufacturer Part Number: BBA-TP4/300



Manufacturer	EATON - MOELLER
MPN / Reference	BBA-TP4/300
Catalog number	Y7-138385
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-B20200110B
Generated	2026-08-06

Product Overview

Incoming set, 4p, 560A, to 300mm²

BBA-TP4/300

Eaton xEffect SASy 60i Enclosures Switch- & Controlgear Enclosure. Incoming set, 4p, 560A, to 300mm²
Connection kit, 60 mm system, poles=4, terminal capacity=95-300mm² MCM 300-MCM 600., I_e=560A, width=180 - 228mm, can be used for rail 20x5/10, 25x5/10, 30x5/10 and double T profile, silicon free, chlorine free, self-extinguishing to UL 94, track resistance CTI 200, temperature resistant to 120 °C, pole pitch adjustable, fixing direct over busbar terminals, including shroud with adjustable width, passing through is not possible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Connection Accessories for Enclosures
--------------	---

Additional Product Information

General specifications

Product Name Eaton xEffect SASy 60i terminal plate Catalog Number 138385 Model Code BBA-TP4/300 EAN 4015081351657 Product Length/Depth 90 mm Product Height 260 mm Product Width 228 mm Product Weight 2.55 kg
Compliances RoHS conform Delivery program

Type Technical data - electrical

Rated operation current (I_e) 560 A Rated operational current 560 A Rated operational current (I_e) - max 560 A Creepage resistance CTI 200

Technical data - mechanical

Material Silicon free, chlorine free Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar width - min 12 mm Busbar width - max 30 mm Terminal capacity (conductor) 95 mm² - 300 mm²

MCM 300 - MCM 600 Conductor cross section - max 300 mm² Width clamp 228 mm Design verification as per IEC/EN 61439 - technical data

Temperature resistance Temperature resistant to 120 °C Additional information

Features Self-extinguishing acc. UL 94 Functions Connection kit

Connections Special features Pole pitch adjustable

Fixing direct over busbar terminals

Including shroud with adjustable width

Looping is possible

Suitable for Round conductor connection

Four-pole

Sector conductor connection

Strip conductor connection

Flat rail Used with 25 mm x 5/10 mm rail

30 mm x 5/10 mm rail

20 mm x 5/10 mm rail

Double T profile

Connection

60 mm system

ETIM for 138385 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

5 mm

Busbar width (EF007219)

12 mm

Suitable for (EF000073)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA-TP4/300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.