

INDUSTRIAL COMPONENT DATA

BBA0-32-PI 199469 EATON ELECTRIC Adapter for busbars 45mm 32A Push-in

Brand: EATON - MOELLER | Manufacturer Part Number: BBA0-32-PI



Manufacturer	EATON - MOELLER
MPN / Reference	BBA0-32-PI
Catalog number	Y7-199469
Category	Busbar adapter
Minimum order	1 Pcs
Document ID	EO-35255375D4
Generated	2026-08-05

Product Overview

Adapter for busbars 45mm 32A; Push-in

45mm busbar adapter for 60mm busbar system, one mounting rail, three prefabricated cables (AWG10/6 square millimeter) for connection of switching device, can be used for motor-protective circuit-breaker PKZM0, PKE and DOL starter/ MSC-D(E)(A) with contactor DILM17 to DILM32, rated operational current: 32A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series BBA Accessory Busbar adapter Catalog Number 199469 Model Code BBA0-32-PI
EAN 4015081978755 Product Length/Depth 260 mm Product Height 73 mm Product Width 45 mm Product Weight 0.301 kg
Certifications CE Delivery program

Type Nominal current 32 A Technical data - electrical

Voltage rating at AC 690 V Rated operation current (Ie) 32 A Electric connection type 3 conductors AWG 10

Push in terminals Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 35 mm Number of DIN rails 1 Busbar distance 60 mm Busbar thickness
- min 5 mm Busbar thickness - max 10 mm Adapter width 45 mm Design verification as per IEC/EN 61439 - technical data
Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Additional information

Special features Terminal capacity: 6 mm² (AWG 10)

ETIM for 199469 Low-voltage industrial controls and switchgear (EC001531)

Feature Name

Feature Value

Mounting rail armament (EF003700)

2 mounting rails

Type of electric connection (EF003961)

3 conductors AWG 10

Rated current In (EF008250)

32 A

Min. busbar thickness (EF006536)

5 mm

Max. busbar thickness (EF003702)

10 mm

Width of the adapter (EF003703)

45 mm

Rail width (EF003704)

35 mm

Busbar distance (EF002638)

60 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA0-32-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.