

INDUSTRIAL COMPONENT DATA

BBA0K-32-PI 199635 EATON ELECTRIC Sweeper adapter 45mm 32A 1TS Push-in

Brand: EATON - MOELLER | Manufacturer Part Number: BBA0K-32-PI



Manufacturer	EATON - MOELLER
MPN / Reference	BBA0K-32-PI
Catalog number	Y7-199635
Category	Busbar adapter
Minimum order	4 Pcs
Document ID	EO-186A1E71D3
Generated	2026-08-03

Product Overview

Sweeper adapter 45mm 32A 1TS; Push-in

45mm busbar adapter for 60mm busbar system, one mounting rail, three prefabricated cables (AWG10/6 square millimeter) for connection of switching device, can be used for motor-protective circuit-breaker PKZM0, PKE contactor or DILM7 to DILM32, rated operational current: 32A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product name Eaton Moeller® series BBA accessory - Busbar adapter Catalogue code 199635 Ean 4015081983360

Product length/depth 200 mm Product height 73 mm Product width 45 mm Product weight 0.224 kg Certification(s) Ec

Model code BBA0K-32-PI Delivery program

type Rated current 32 A Technical data - electrical

AC voltage rating 690 V Rated operating current (Ie) 32 A Type of electrical connection 3 Conductors AWG 10

Push-in terminals Technical data - mechanical

DIN rail configuration 1 x Fixed Mounting Rail Guide width 20 mm Number of DIN Rails 1 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Adapter width 45 mm Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Additional information

Special features Clamp capacity: 6 mm² (AWG 10)

ETIM for 199635 Low-voltage industrial controls and switchgear (EC001531)

Feature Name

Feature Value

Mounting rail armament (EF003700)

1 mounting rail

Type of electric connection (EF003961)

3 conductors AWG 10

Rated current In (EF008250)

32 A

Min. busbar thickness (EF006536)

5 mm

Max. busbar thickness (EF003702)

10 mm

Width of the adapter (EF003703)

45 mm

Rail width (EF003704)

20 mm

Busbar distance (EF002638)

60 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA0K-32-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.