

INDUSTRIAL COMPONENT DATA

BBA4-63 101457 Y7-101457 EATON ELECTRIC Adapter bar distributor, 55mm, 63A, 1 THESSALONIANS

Brand: EATON - MOELLER | Manufacturer Part Number: BBA4-63



Manufacturer	EATON - MOELLER
MPN / Reference	BBA4-63
Catalog number	Y7-101457
Category	Busbar adapter
Minimum order	4 Pcs
Document ID	EO-5A1364DBEF
Generated	2026-08-05

Product Overview

Adapter bar distributor, 55mm, 63A, 1 THESSALONIANS

BBA4-63

Eaton Moeller® series BBA Busbar adapter, 54 mm, 63 A, DIN rail: 1

55mm busbar adapter for 60mm busbar system, one mounting rail, three prefabricated cables (AWG8/10 square millimeter) for connection of switching device, can be used for motor-protective circuit-breaker PKZM4, PKE65, rated operational current: 63A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series BBA Accessory Busbar adapter Catalog Number 101457 Model Code BBA4-63 EAN 4015081013777 Product Length/Depth 200 mm Product Height 63 mm Product Width 55 mm Product Weight 0.347 kg

Certifications UL

CSA-C22.2 No. 14

UL 508

UL File No.: E300273

CE

Certified by UL for use in Canada

IEC60439-1

UL Category Control No.: NMTR; NMTR7

UL 508A Delivery program

Type Nominal current 63 A Technical data - electrical

Voltage rating (UL CSA 13) 600 V AC, UL/CSA Voltage rating at AC 690 V Rated operation current (Ie) 63 A Electric connection type Round conductor Technical data - mechanical

Mounting rail armament 1 mounting rail Rail width 35 mm Number of DIN rails 1 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Adapter width 55 mm Design verification as per IEC/EN 61439 - technical data Equipment heat dissipation, current-dependent P_{vid} 6.9 W Static heat dissipation, non-current-dependent P_{vs} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal h...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA4-63 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.