

INDUSTRIAL COMPONENT DATA

BBS-3/FL-NA 107067 Y7-107067 EATON ELECTRIC Busbar support, 3p, for flat busbars

Brand: EATON - MOELLER | Manufacturer Part Number: BBS-3/FL-NA



Manufacturer	EATON - MOELLER
MPN / Reference	BBS-3/FL-NA
Catalog number	Y7-107067
Category	Busbar support
Minimum order	10 Pcs
Document ID	EO-DC0EE9368A
Generated	2026-08-04

Product Overview

Busbar support, 3p, for flat busbars

BBS-3/FL-NA

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Busbar support, 3p, for flat busbars, NA IEC busbar support, 60 mm system, rated operational current $I_e=630A$, poles=3, can be used for 12x5/10, 20x5/10 and 30x5/10, with slider to adapt to the respective busbar size, with screw block inside, temperature resistant to 120 °C, track resistance CTI 200, self-extinguishing to UL 94, RAL 7035, thermoplastic, silicon free, chlorine free, halogen free, distance between busbar supports corresponding to short-circuit strength diagram, UL approved

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure Catalog Number 107067 Model Code BBS-3/FL-NA EAN 4015081069200 Product Length/Depth 50 mm Product Height 190 mm Product Width 20 mm Product Weight 0.149 kg Compliances IEC 60439-1

UL508A

CE marking

CSA-C22.2 No. 14

UL CSA09 (refer to approbation report)

RoHS conform Certifications CSA (Class No. 3211-37)

CSA (File No. 236217)
Specially designed for North America
UL (File No. E300273)
North America (UL listed, CSA certified)
UL (Category Control Number NMTR, NMTR7) Delivery program
Type Color Light gray (RAL 7035) Number of poles Three-pole Technical data - electrical
Voltage rating (UL CSA 13) Max. 600 V AC Current rating - max 630 A Rated operation current (Ie) 630 A Creepage
resistance CTI 200 Technical data - mechanical
Material Thermoplast, silicon free, chlorine free
Halogen free Degree of protection Feeder circuits Busbar distance 60 mm Design verification as per IEC/EN 61439 -
technical data
Temperature resistance Up to 120 °C Ambient operating temperature - max 35 °C Additional information
Features Halogen free
Self-extinguishing acc. UL 94 Functions Busbar support
UL busbar support
Current limiting circuit breaker, refer to approbation report Special features Can be fitted to all busbar sizes using concertina
system
With screw block inside
Suitable for Three-pole Used with 30 x 5/10 mm
12 x 5/10 mm
Feeder circuits
20 x 5/10 mm
System for flat busbar
60 mm system
ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBS-3/FL-NA with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.