

INDUSTRIAL COMPONENT DATA

BeamLite II 2x200lm 1h BL2MC-C1 EATON ELECTRIC

BeamLite II 2x200lm 1h

Brand: EATON - MOELLER | Manufacturer Part Number: BeamLite II 2x200lm 1h



Manufacturer	EATON - MOELLER
MPN / Reference	BeamLite II 2x200lm 1h
Catalog number	BL2MC-C1
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-0248D512C0
Generated	2026-08-05

Product Overview

BeamLite II 2x200lm 1h

Eaton BeamLite II self-contained stand alone, 1h emergency duration with eFocus (narrow & wide illumination, programmed by user), 400 lumens, IP65 degree of protection, class II insulation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self contained
--------------	----------------------------------

Additional Product Information

ETIM for BL2MC-C1 Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

None

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

NiCd

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

Yes

Suitable for number of light sources (EF006436)

2

Lamp holder (EF000048)

None

Number of lighting heads (EF004258)

2

Housing material (EF001596)

Plastic

Housing colour (EF000136)

White

Material cover (EF004284)

Plastic transparent

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

LED driver constant current

Light distributor (EF012170)

Refractor lens

Degree of protection (IP) (EF005474)

IP65

Impact strength (EF004293)

IK07

Protection class according to IEC 61140 (EF000004)

II

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

5 °C

Max. system power (EF009347)

1.6 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

400 lm

Power factor (EF025740)

0.7

Nominal operation time (EF012518)

1 h

Width (EF000008)

178 mm

Height/depth (EF001456)

106 mm

Length (EF001438)

417 mm

Type of wiring (EF011868)

Suitable for through wiring

Number of poles (EF001391)

3

Conductor cross section (EF000085)

1.5 mm²

Connection type (EF000124)

Plug-in connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BeamLite II 2x200lm 1h with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.