

INDUSTRIAL COMPONENT DATA

BeamTech Large 4x500lm 1h CGL BT4LL-G1CGL EATON

ELECTRIC BeamTech Large 4x500lm 1h CGL

Brand: EATON - MOELLER | Manufacturer Part Number: BeamTech Large 4x500lm 1h CGL



Manufacturer	EATON - MOELLER
MPN / Reference	BeamTech Large 4x500lm 1h CGL
Catalog number	BT4LL-G1CGL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-30ADF686BE
Generated	2026-08-04

Product Overview

BeamTech Large 4x500lm 1h CGL

Eaton BeamTech, large power supply with 4 light heads self-contained monitored CGL+, 1h emergency duration with eFocus (narrow & wide illumination, programmed by user), 2000 lumens, IP65 degree of protection, class II insulation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

Additional Product Information

ETIM for BT4LL-G1CGL Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)
Lithium-ions
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
4
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
4
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Plastic transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
Not required
Light distributor (EF012170)
Refractor lens
Degree of protection (IP) (EF005474)
IP65
Impact strength (EF004293)
IK07
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
2 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
2000 lm
Luminous flux in standby mode (EF011954)
3 lm
Power factor (EF025740)
0.42
Nominal operation time (EF012518)
1 h
Width (EF000008)

310 mm

Height/depth (EF001456)

69 mm

Length (EF001438)

466 mm

Built-in height/depth (EF023518)

36 mm

Built-in length (EF004265)

451 mm

Type of wir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BeamTech Large 4x500lm 1h CGL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.