

INDUSTRIAL COMPONENT DATA

BeamTech Small 2x250lm 1h CGL BT2SC-D1CGL EATON ELECTRIC BeamTech Small 2x250lm 1h CGL

Brand: EATON - MOELLER | Manufacturer Part Number: BeamTech Small 2x250lm 1h CGL



Manufacturer	EATON - MOELLER
MPN / Reference	BeamTech Small 2x250lm 1h CGL
Catalog number	BT2SC-D1CGL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-48164B07CB
Generated	2026-08-03

Product Overview

BeamTech Small 2x250lm 1h CGL

Eaton BeamTech, small power supply with 2 light heads self-contained monitored CGL+, 1h emergency duration with eFocus (narrow & wide illumination, programmed by user), 500 lumens, IP65 degree of protection, class II insulation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

ETIM for BT2SC-D1CGL Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

No

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

NiCd

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

Yes

Suitable for number of light sources (EF006436)

2

Lamp holder (EF000048)

None

Number of lighting heads (EF004258)

2

Housing material (EF001596)

Plastic

Housing colour (EF000136)

White

Material cover (EF004284)

Plastic transparent

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

Not required

Light distributor (EF012170)

Refractor lens

Degree of protection (IP) (EF005474)

IP65

Impact strength (EF004293)

IK07

Protection class according to IEC 61140 (EF000004)

II

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

5 °C

Max. system power (EF009347)

1.6 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

500 lm

Power factor (EF025740)

0.7

Nominal operation time (EF012518)

1 h

Width (EF000008)

155 mm

Height/depth (EF001456)

69 mm

Length (EF001438)

466 mm

Type of wiring (EF011868)

Suitable for through wiring

Number of poles (EF001391)

3

Conductor cross section (EF000085)

1.5 mm²

Connection ty...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BeamTech Small 2x250lm 1h CGL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.