

INDUSTRIAL COMPONENT DATA

BeamTech Small 2x500lm 1h AT BT2SL-F1-AT EATON

ELECTRIC BeamTech Small 2x500lm 1h AT

Brand: EATON - MOELLER | Manufacturer Part Number: BeamTech Small 2x500lm 1h AT



Manufacturer	EATON - MOELLER
MPN / Reference	BeamTech Small 2x500lm 1h AT
Catalog number	BT2SL-F1-AT
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-D610654A15
Generated	2026-08-05

Product Overview

BeamTech Small 2x500lm 1h AT

Eaton BeamTech,small power supply with 2 light heads self-contained with Autotest functionality,1h emergency duration with eFocus (narrow & wide illumination,programmed by user),1000 lumens,IP65 degree of protection,class II insulation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self contained
--------------	----------------------------------

Additional Product Information

ETIM for BT2SL-F1-AT Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Function (EF000030)

Suitable for labelling type (EF001277)

Other

Type of indicator (EF001278)

With pictogram (EF011099)

false

Monitoring equipment (EF008091)

Automatic self test

Suitable for standby switching (EF017055)

Suitable for continuous circuit (EF017056)
With remote switch connection (EF007947)
true
With remote control (EF000483)
Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
Lithium-ion
Lamp type (EF002423)
LED not exchangeable
With light source (EF005905)
true
Suitable for number of light sources (EF006436)
2
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
2
Housing material (EF001596)
Plastic
RAL-number housing (EF012502)
Housing colour (EF000136)
White
Material cover (EF004284)
Plastic, transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Nominal current (EF009345)
None mA
Type of control gear (EF000381)
Not required
Exchangeable control gear (EF016286)
Light distributor (EF012170)
Refractor lens
Max. number of luminaires per miniature circuit breaker B16 (MCB) (EF015534)
Energy efficiency class of the light source according to EU regulation 2019/2015 (EF016835)
Max. number of luminaires per miniature circuit breaker C16 (MCB) (EF015533)
Rated life time L70/B50 at 25 °C (EF011870)
None h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) (EF015687)
None %
Lumen main...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BeamTech Small 2x500lm 1h AT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.