

INDUSTRIAL COMPONENT DATA

BF-UT-4/96-C 103118 Y7-103118 EATON ELECTRIC Complete flush-mounted flat distribution board with window, whi..

Brand: EATON - MOELLER | Manufacturer Part Number: BF-UT-4/96-C



Manufacturer	EATON - MOELLER
MPN / Reference	BF-UT-4/96-C
Catalog number	Y7-103118
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-D515B62E8B
Generated	2026-08-04

Product Overview

Complete flush-mounted flat distribution board with window, white, 24 SU per row, 4 rows, type C
BF-UT-4/96-C

Eaton xComfort BF LV systems Final Distribution Boards. Complete flush-mounted flat distribution board with window, white, 24 SU per row, 4 rows, type C

Complete BF-U-./..-C flush-mounted distribution board, white RAL 9016, 24 space units per row, 4 rows, height 770mm, width 588 mm, depth 136 mm, including door and transparent panel, front plates, DIN-rail mounting frame and neutral/PE terminals. Enclosure: closed design, including back plate, back plate can be used as a fixing plane, 2 cable gland plate inserts for slim distribution boards with a width of 24 space units, top, knockout cable entry openings on the bottom, terminals pre-assembled on enclosure (no loss of space units). Wall trough with door frame, back plate can be used as a fixing plane, cable entry openings that are easy to knock out, 127 mm depth, terminals pre-assembled on enclosure (no loss of space units), 4 side fixing brackets. Sheet steel door with cam lock and transparent panel included as standard, sheet steel door with expanded depth (required, for example, in order to install RMQ components in the door) (BFZ-OTR-./...) is available as an accessory. Removable DIN-rail mounting frame, for 45 mm modular installation devices, 150 mm DIN busbar distance, Eaton circuit-breakers can be integrated w...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

General specifications

Product Name Eaton xComfort BF small distribution board Catalog Number 103118 Model Code BF-UT-4/96-C EAN

4015081029570 Product Length/Depth 800 mm Product Height 160 mm Product Width 615 mm Product Weight 12.6 kg
Compliances RoHS conform Certifications IEC/EN 61439-1
IEC/EN 62208
IEC/EN 61439-3 Delivery program
Type Basic device BF flat DBO Installation distribution boards Application Indoor (installation site) Color Traffic white (RAL 9016)
White Technical data - electrical
Voltage rating at AC 415 V AC Frequency rating of contacts 50 Hz / 60 Hz Technical data - mechanical
Closure type Other Enclosure material Steel Width in number of modular spacings 24 Mounting method Flush mounting
DIN-rail
Flush mounted (plaster)
Hollow-wall mounting and flush mounting Material Sheet steel, powder-coated Degree of protection IP30
IK07 (impact resistance) Number of module space units per row 24 Number of rows 4 Terminal type Screw terminals PE
and N terminal number and cross section PE: 2 x 25 mm² + 43 x 16 mm²
N: 2 x 25 mm² + 43 x 16 mm² Built-in depth 127 mm Built-in height 720 mm Built-in width 560 mm Internal depth 127 mm
Cable entry position Cable entries on top and bottom Cover/door color Transparent
White Cover/door model With notch Cover/door type Door
Single Module rack type Rail frame Protective shrouding material Metal Temperature-rise verification as per IEC 60890
Heat diss. ambient 35°C delta T: 20°C flush mount individ. encl. top (IEC 60890) 48 W Heat dis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BF-UT-4/96-C with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.