


INDUSTRIAL COMPONENT DATA

Z-SV-10/N-1TE/13 264917 Y7-264917 EATON ELECTRIC Block busbar 1Ph., for PLN. (1HP), Z-SI, flat blue

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV-10/N-1TE/13



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV-10/N-1TE/13
Catalog number	Y7-264917
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-1B7EBB2953
Generated	2026-08-06

Product Overview

Block busbar 1Ph., for PLN. (1HP), Z-SI, flat blue

Z-SV-10/N-1TE/13

Eaton Distribution parts. Block busbar 1Ph., for PLN. (1HP), Z-SI, flat blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 264917 Model Code Z-SV-10/N-1TE/13 EAN 4015082649173

Product Length/Depth 28 mm Product Height 6 mm Product Width 232 mm Product Weight 0.038 kg Compliances RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Pin Rated surge voltage 4 kV Rated uninterrupted current (Iu) 50 A Suitable for number of devices 19 Number of poles Two-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 1 Number of phases 1 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 0 kA

ETIM for 264917 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

1
Number of poles (EF001391)
2
Suitable for number of devices (EF007241)
19
Module width (EF007504)
0 mm
Cross section (EF000649)
10 mm²
Length (EF001438)
28 mm
Can be cut to size (EF015250)
Yes
Width in number of modular spacings (EF002950)
1
Rated permanent current I_u (EF001389)
50 A
Type of electric connection (EF003961)
Pin
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
4 kV
Conditioned rated short-circuit current I_q (EF001444)
0 kA
Max. rated operation voltage U_e (EF007357)
415 V
Rated short-time withstand current I_{cw} (EF007050)
0 kA
Suitable for devices with N-conductor (EF007218)
No
Suitable for devices with auxiliary switch (EF007217)
No
Colour....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV-10/N-1TE/13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.