

INDUSTRIAL COMPONENT DATA

Z-SV/UL-16/3P-3TE/12 104899 Y7-104899 EATON ELECTRIC Block busbar 3Ph., 12HP, for FAZ-NA, FAZ-RT

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV/UL-16/3P-3TE/12



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV/UL-16/3P-3TE/12
Catalog number	Y7-104899
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-1B98ACF119
Generated	2026-08-06

Product Overview

Block busbar 3Ph., 12HP, for FAZ-NA, FAZ-RT

Z-SV/UL-16/3P-3TE/12

Eaton Distribution parts. Block busbar 3Ph., 12HP, for FAZ-NA, FAZ-RT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 104899 Model Code Z-SV/UL-16/3P-3TE/12 EAN 4015081047093

Product Length/Depth 206 mm Product Height 46 mm Product Width 15.5 mm Product Weight 0.154 kg Compliances RoHS conform Certifications UL 489

Specially designed for North America for large creepage and creepage distances

UL (Category Control Number NMTR2, DIHS2)

UL listed

IEC/EN 60898

UL (File No. E257181)

CE marking Product specifications

Type Features Insulated Accessory/spare part type Busbar for combined residual current/power circuit breaker

Busbar for residual current circuit breakers

Busbar for miniature circuit breaker Electric connection type Pin Used with Feeder Circuit, Branch Circuit

Busbar

Z-SV Rated surge voltage 9.5 KV Rated uninterrupted current (Iu) 0 A Suitable for number of devices 4 Application Switchgear for industrial and advanced commercial applications Number of poles Three-pole Color Other Degree of protection IEC/EN 60898; UL 489; CE marking

IEC: IP20, UL/CSA Type: - Rated short-time withstand current (Icw) 0 kA Voltage rating (UL CSA 13) Refer to main components FAZ, FAZ-NA, FAZ-RT Cross section 16 mm² Number of modular spacings 3 Number of phases 3 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 690 V Rated conditional short-circuit current (Iq) 0 kA Functions

Busbar

ETIM for 104899 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV/UL-16/3P-3TE/12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.