

INDUSTRIAL COMPONENT DATA

Z-SV-35/3P+N-6TE 263110 Y7-263110 EATON ELECTRIC Block busbar 4Ph., for Z-SLS, PLHT D0.-SO/.., PLHT-V (1, 5s..

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV-35/3P+N-6TE



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV-35/3P+N-6TE
Catalog number	Y7-263110
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-7378783B05
Generated	2026-08-06

Product Overview

Block busbar 4Ph., for Z-SLS, PLHT D0.-SO/.., PLHT-V (1, 5space units)

Z-SV-35/3P+N-6TE

Eaton Distribution parts. Block busbar 3Ph.+N, for Z-SLS, PLHT D0.-SO/.., PLHT-V (1, 5space units)

Block busbar 3Ph.+N, for Z-SLS, PLHT D0.-SO/.., PLHT-V (1.5SU)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 263110 Model Code Z-SV-35/3P+N-6TE EAN 4015082631109

Product Length/Depth 429 mm Product Height 38.4 mm Product Width 25 mm Product Weight 0.591 kg Compliances RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Pin Rated surge voltage 4 KV Rated uninterrupted current (Iu) 110 A Suitable for number of devices 0 Number of poles Four-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 35 mm² Number of modular spacings 16 Number of phases 4 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 0 kA Suitable for 4 devices

ETIM for 263110 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

4

Number of poles (EF001391)

4

Suitable for number of devices (EF007241)

0

Module width (EF007504)

0 mm

Cross section (EF000649)

35 mm²

Length (EF001438)

429 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

16

Rated permanent current I_u (EF001389)

110 A

Type of electric connection (EF003961)

Pin

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short-circuit current I_q (EF001444)

0 kA

Max. rated operation voltage U_e (EF007357)

415 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

No

Suitable for devices with auxiliar...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV-35/3P+N-6TE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.